





**PHOTOSENSITIVE LITHOGRAPHIC PLATE**

**Patent number:** JP59053836  
**Publication date:** 1984-03-28  
**Inventor:** TOYAMA TADAO; KOBAYASHI KESANAO; KOIKE MITSURU; TAMOTO KOUJI  
**Applicant:** FUJI PHOTO FILM CO LTD  
**Classification:**  
- **international:** G03C1/52; G03C1/71; G03F7/10  
- **european:** G03F7/033; G03F7/095P  
**Application number:** JP19820164435 19820921  
**Priority number(s):** JP19820164435 19820921

**Also published as:**

 EP0104863 (A2)  
 US4687727 (A1)  
 EP0104863 (A3)  
 EP0104863 (B1)

**Report a data error here**

**Abstract of JP59053836**

**PURPOSE:** To improve stability of sensitivity during plate making, by using a combination of a photopolymerizable compsn. contg. a specified photosensitive polymer and a diazo resin.

**CONSTITUTION:** A photopolymerizable compsn. layer formed on at least one side of a support consists of (A) a polymer having in the side chains unsatd. groups, each represented by the general formula, and a carboxyl group, (B) a monomer or oligomer having at least two polymerizable ethylenically unsatd. double bonds on the basis of monomer, (C) a photopolymn. initiator, and (D) a diazo resin, such as 2-methoxy-4-hydroxy-5-benzoyl-benzenesulfonate produced by condensation of 4-diazo-diphenylamine and formaldehyde. As (B), pentaerythritol tetraacrylate, etc. are used, and as (A), allyl methacrylate/methacrylic acid copolymer in 85/15 molar ratio, etc. are used.

---

Data supplied from the **esp@cenet** database - Worldwide